



Technical Datasheet INOX MX 3 AEROSOL

Revised Date: January 2015

Description

INOX MX 3 is a general purpose lubricant that can be used in many different industries with many different applications. It contains no silicone, acid, kerosene or diesel. INOX MX 3 is non-conductive, non-static, non-toxic, non-corrosive and non-staining. It also does not harm metal points or surfaces, plastics, paints, enamels, fibreglass, formica or neoprene seals and will not wash off with water.

Applications

- *Automotive & Transport
- *Industrial
- *Sports
- *Marine
- *Manufacturing
- *Engineering
- *Electrical & Electronics
- *Farming & Mining
- *Firearms
- *Domestic
- *Commercial
- *Aviation

Product Features

Density @ 15.6°C	850
Pour Point	-13°C
Fire Point	204°C
Dielectric	>40
Karl Fisher Water	273.2ppm
Viscosity @ 40°C	10.04
@ 100°C	2.54
Agency Approvals	ASTM1298
	ASTM D97
	ASTM D92
	ASTM D1744
	ASTM D445

Storage

INOX MX 3 is classified as a Flammable Gas for storage and handling purposes. Store in a cool, dry, well ventilated area, out of direct sunlight. Avoid sparks, flames and other ignition sources

Presentation

INOX MX 3 is available in a 300gram Aerosol Can.

Health & Safety in Use

Use in a well ventilated area with the use of safety goggles, gloves and face shield where required.

For more handling safety information on this product, please consult the Material Safety Data Sheet. MSDS