



Technical Datasheet

INOX MX 5 PLUS AEROSOL

Revised Date: January 2015

Description

INOX MX 5 PLUS is a premium grade extreme pressure anti-friction medium which gives increased lubrication ability between the contact surfaces. This reduced friction environment also lowers operating temperatures. It will not become tacky, alter surface tolerances, dry out or wash off with water. is non-toxic, non-conductive, non-corrosive and non-staining

Applications

- *Car and Motorcycles
- *Truck, Bus & Trailer
- *Cold Climate Lubricant
- *Electrical
- *Farming
- *General
- *Hobbies
- *Industrial & Mining
- *Marine & Shipping
- *Recreational Users

Product Features

Density @ 15.6°C	865
Pour Point	-13°C
Fire Point	204°C
Dielectric	33
Karl Fisher Water	254.4ppm
Viscosity @ 40°C	10.86
@ 100°C	2.74
Timken, OK Load kg	20
4 – Ball weld test - Kgf	275
Agency Approvals	ASTM1298
	ASTM D97
	ASTM D92
	ASTM D1744
	ASTM D445
	ASTM D2509
	ASTM IP239

Storage

INOX MX 5 PLUS is classified as a Flammable Gas for storage and handling purposes. Store in a cool, dry, well ventilated area, out of direct sunlight. Avoid sparks, flames and other ignition sources

Presentation

INOX MX 5 PLUS is available in a 300gram Aerosol Can.

Health & Safety in Use

Use in a well ventilated area with the use of safety goggles, gloves and face shield where required.

For more handling safety information on this product, please consult the Material Safety Data Sheet. MSDS